



# Fibromax<sup>®</sup> Pro Paint

Ready-to-paint MDF  
with a paint grade film

Fibromax Pro Paint is MDF with an excellent millable core. The board has highquality paint grade film on both sides, so that you can paint, spray or lacquer it without pre-treatment using solvent or water-based paint. These boards can be used in service class 1 (dry environments) and can only be used in biological hazard class 1 of Standard EN-335-3.

## Applications

- Interior decoration
- Furniture production

## Characteristics



L-MDF (EN 622-5)



Ready to paint



# Fibromax<sup>®</sup> Pro Paint

## Applications

Thanks to their strong technical characteristics and ease of use, the versatile Fibromax Pro Paint boards are suitable for many applications in the furniture industry, shop interiors and interior design. These boards have an easy-finish surface for kitchens, walk-in wardrobes and bathrooms as well as sliding doors and partition walls. This board is also often used in shop and office furnishings. Fibromax Pro Paint is a board that can be finished in a final colour of your choice without pre-treatment. Furthermore, Fibromax Pro Paint ensures excellent adhesion, fewer layers of paint for a perfect result and uniform paint absorption.

## Technical specifications

General characteristics + Standard	Unit	Average values						
Thickness EN 324-1	mm	8	10	12	16	19	22	25
Technical characteristics + Standard		5/95 percentile values						
Bending strength EN 310	N/mm <sup>2</sup>	20	20	20	18	18	15	15
Bending stiffness EN 310	N/mm <sup>2</sup>	1700	1700	1700	1600	1600	1500	1500
Internal bond EN 319	N/mm <sup>2</sup>	0,45	0,45	0,45	0,45	0,45	0,45	0,45
Swelling/24h EN 317	%	20	16	16	14	14	12	12

Fibromax Pro Paint meets the general requirements and comes under formaldehyde emission class E1 as described in Table 1 of EN Standard 622-1.

## Available dimensions and thicknesses

Fibromax Pro Paint is available from stock.

Consult the complete UNILIN Panels stock range at [www.unilinpanels.com](http://www.unilinpanels.com).

For our technical capabilities on custom thicknesses and dimensions, as well as minimum order requirements, please contact our sales team or email [info.panels@unilin.com](mailto:info.panels@unilin.com).

## Certificates

UNILIN Division Panels is actively committed to sustainable forest management.

Fibromax Pro Paint is available on demand with PEFC and FSC labelling.

