



# UNILIN Evola-Belspan High Performance

Melamine faced, non-structural chipboard for interior and furniture, suitable for heavy-duty surfaces thanks to the product's multi-layer structure

This product satisfies the surface specifications of a base board, bonded on two sides with a HPL. The melamine faced, high-performance board can be used in dry conditions, service class 1 and is made from 100% recovered wood.

## Applications

- Interior design
- Heavy-duty use
- Horizontal application

## Properties



Standard P2 chipboard



Melamine faced chipboard



100% recovered wood



Anti-bacterial



# UNILIN Evola-Belspan High Performance

## Applications

Applications with heavy-duty use of panels and suitable for any application in which bonded HPL can be used – shop fitting, public spaces, hotels, work surfaces, office furniture, schools, hospitals, residential care facilities, etc. The board is suitable for use in indoor environments.

## Advantages

- Budget-friendly alternative to two-side bonded board with HPL
- Time-saving, bonding step is superfluous
- Higher return and optimisation options thanks to larger dimensions (2800 x 2070)
- Fewer joints thanks to larger dimensions (2800 x 2070)
- Better adhesion when compared to two-side bonded board with HPL

## Technical specifications

Technical specifications can be found on [unilinpanels.com](http://unilinpanels.com).

## Finish

The melamine faced, high-performance board can be combined with solid designs\* from the UNILIN Decorative range. Designs are based on international trends, allowing creativity to run free when tackling interior projects.

\*does not apply to MST (supermat) references

## Available dimensions and thicknesses

The standard size is 2800 x 2070, with a standard thickness of 19 mm. Colour WE28BST (Everest white topmat) from the standard range can be collected within five working days, starting from a volume of one pack. Other designs are available on request.