

CLICWALL CORNER FINISHING

Inspiration on how to finish
your Clicwall panels

As well as ensuring that your walls are installed with efficiency and sustainability in mind, you can choose from plenty of quick-fit finishing options for corners, windows, and doors for an elegant flourish.

Inner corners



Open joint: quick and simple

Ideal when conditions are dry. During installation, leave a few millimetres free between the Clicwall wall panels for a stylish look.

Sealed inner joint: quick and waterproof

The smart choice, especially for humid environments that call for optimum protection. During installation, keep a few millimetres free between the panels and glue together afterwards for a complete seal.

- Kit adapted to installation area
- Available from dealer



Aluminium inner corner profile: for a dash of elegance

Want to add a touch of something special? This stylish inner corner profile is the answer.

- Available lengths: 2785 mm and 3500 mm (10 pcs)
- Black/white/aluminium in stock
- Lacquered in preferred colour on request

Flexible MDF profile: for rapid inner corner and expansion joint finishing

Ideal for modular units.

- Available length: 2750mm (10 pcs)
- Available in the following colours: 00025 CST, 00025 W03, 0F989 BST, 0H163 BST, 0H450 V9A, 0H588 V8A, 0H784 W06, 0H786 W06, 0U127 CST, 0U174 CST or go for a paintable version with high-quality white primer layer.
- Other colours available on request



External corners



Edged panels: for a quality finish that combines aesthetics with sustainability

Simply remove the tongue from the panel and use the matching edging tape from Unilin for finishing.

- 23x1 mm - 75 m/roll
- The full Unilin Decorative Range available in ABS edging tape
- Other colours on request

Aluminium external corner profile: streamlined and refined

During installation, place the profile between the Clicwall panels to ensure seamless finishing.

- Available lengths: 2785 mm and 3500 mm (10 pcs)
- Black/white/aluminium in stock
- Lacquered in preferred colour on request



Aluminium L-profile: for rapid, impact-resistant finishing

Conceal open edges with ease by fitting an aluminium profile after installation. This profile offers long-term protection.

- Available lengths: 2785 mm and 3500 mm (10 pcs)
- Black/white/aluminium in stock
- Lacquered in preferred colour on request

MDF exterior corner profile: for rapid exterior corner and expansion joint finishing

Ideal for modular units.

- Available lengths: 2750 mm (10 pcs)
- Available in the following colours: 00025 CST, 00025 W03, OF989 BST, OH163 BST, OH450 V9A, OH588 V8A, OH784 W06, OH786 W06, OU127 CST, OU174 CST or go for a paintable version with high-quality white primer layer.
- Other colours available on request



CLICWALL CORNER FINISHING



Unilin Panels

Ingelmunstersteenweg 229
8780 Oostrozebeke
Belgium
T +32 56 66 70 21
info.panels@unilin.com
www.unilinpanels.com