

Clicwall[®] Paint







Decorative wallcovering, ready to paint.

Non-structural MDF board with Uniclic profile, with a high-quality white paint grade film, suitable for an excellent and cost and time saving paint finish. Clicwall Paint is suitable for dry conditions, service class 1, mainly used for separation walls and wall linings. Clicwall Paint is made from 100% recovered wood.

Applications

- Separation walls
- Wall linings

Characteristics

-  MDF (EN 14322)
-  A wide selection of designs
-  Perfect for intensive use
-  Quick installation for an immediate stylish result
-  Tongue and groove
-  100% recovered wood



Clicwall[®] Paint

Applications

Melamine faced non-structural MDF board, ready to paint, for separation walls and wall linings.

Long sides provided with Uniclic profile resulting in a fast and easy click system.

Impact proof which makes Clicwall Paint suitable for projects in retail, hotel, holiday homes, modular units, office, senior homes, education, etc.

Clicwall Paint is conform Euroclass D-s2,d0 (non fire retardant application) and can be used in non humid conditions (service class 1).

Available dimensions / thicknesses

Dimensions: Net/gross (HxWxD):

- Clicwall standard: 2785x600x10mm / 2785x618x10mm; 13kg/panel
 - Clicwall high panels: 3500x600x10mm / 3500x618x10mm; 16kg/panel
- Other dimensions: on request.

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Clicwall Paint is standard PEFC labelled and is available on demand with FSC labeling.

Carb II / TSCA VI on demand.