

# UNILIN Evola-Fibralux® MR Black

Melamine faced moisture-resistant and structural MDF board for interior- and furniture available in an extensive range of UNILIN Evola designs

Melamine faced high density, moisture resistant MDF board (MDF.HLS according EN 622-5) with a hard, fine and smoothly sanded surface. The panel is coloured black in the mass. UNILIN Evola-Fibralux MR Black can be used for load bearing applications in humid conditions. This board has low formaldehyde emission (E1 class). UNILIN Evola-Fibralux MR Black is made from 100% recovered wood.

#### **Applications**

- Interior decoration
- Furniture production

#### **Characteristics**



Melamine faced MDF board



Coloured black in the mass



100% recovered wood





## UNILIN Evola-Fibralux® MR Black

#### **Advantages**

Surprising colour effect thanks to the contrast in colour between the top layer and the black board. In perfect colour match with HPL & edging tape for all UNILIN Evola stockrange decors.

- Application in humid conditions
- Easy to clean
- Resistant to UV light
- Budget friendly alternative for 2 sided glued HPL on a black support board
- Easy to process
- 100% recovered wood

#### **Finish**

The melamine faced board is possible to have in combination with a wide variety of designs. The wood decors not only look incredibly lifelike, also the structures feel particularly authentic. Combined with plain colours, basis on international trends, the designs deliver unprecedented freedom in creativity for interior projects.

#### Available dimensions / thicknesses

All designs in the UNILIN Decorative range are available in combination with UNILIN Evola-Fibralux MR black board. The standard size is 2800 x 2070.

Thicknesses 18 and 19 mm are part of the fast lane service range and can be collected within ten or fifteen working days, starting from a volume of two units.

### Certificates

UNILIN Division Panels is actively committed to sustainable forest management. UNILIN Evola-Fibromax MR Black is available on demand in PEFC and/or FSC labelling.

