

DECLARATION OF PERFORMANCE	
Reference :	DOPFlameshieldP5SupremeDeluxeTGv1
Commercial name :	Flameshield P5 Supreme Deluxe TG
Product type :	Melamine faced tongue and groove panel
Reference standard :	Wood Based Panel - EN13986:2004+A1:2015 Annex A Table A.4
CE Class :	P5
Field of application :	Internal use as a structural component in dry conditions
AVCP Class :	2+
Certification number:	1161-CPR-1533
Produced at:	Breestraat 4,B-8710 Wielsbeke Ingelmunstersteenweg 299,B-8780 Oostrozebeke

Essential Characteristic	Unit	Reference	Thickness range (mm)		
			25	>25-32	>32
Bending strength	N/mm <sup>2</sup>	EN 312-table 9	14	12	10
Modulus of elasticity in bending	N/mm <sup>2</sup>	EN 312-table 9	2150	1900	1700
Internal bond	N/mm <sup>2</sup>	EN 312-table 9	0,40	0,35	0,30
Swelling in thickness, 24h	%	EN 312-table 9	10	10	9
Formaldehyde emission class	Class	EN 13986-table B1	E1	E1	E1
Reaction to fire	Class	EN 13501-1	B-s2,d0	B-s2,d0	B-s2,d0
Reaction to fire (Flooring)	Class	EN 13501-1	B <sub>f1</sub> -s1	B <sub>f1</sub> -s1	B <sub>f1</sub> -s1
Water vapour permeability μ	wet	EN 13986 - table 9	15	15	15
	dry		50	50	50
Airborne sound insulation	dB	EN 13986-5.10	NPD	NPD	NPD
Sound absorption α		EN 13986 - table 10	0,10/0,25	0,10/0,25	0,10/0,25
Thermal conductivity λ	W/m.K	EN 13986 - table 11	0,13	0,12	0,12
Strength - tension f <sub>t</sub>	N/mm <sup>2</sup>	EN 12369-1	7,4	6,6	5,6
Strength - compression f <sub>c</sub>	N/mm <sup>2</sup>	EN 12369-1	10,3	9,8	8,5
Strength - bending f <sub>m</sub>	N/mm <sup>2</sup>	EN 12369-1	11,7	10	8,3
Strength - panel shear f <sub>y</sub>	N/mm <sup>2</sup>	EN 12369-1	5,9	5,2	4,8
Strength - planar shear f <sub>r</sub>	N/mm <sup>2</sup>	EN 12369-1	1,5	1,3	1,2
Stiffness - tension E <sub>t</sub>	N/mm <sup>2</sup>	EN 12369-1	1800	1500	1400
Stiffness - compression E <sub>c</sub>	N/mm <sup>2</sup>	EN 12369-1	1800	1500	1400
Stiffness - bending E <sub>m</sub>	N/mm <sup>2</sup>	EN 12369-1	3000	2600	2400
Stiffness - panel shear G <sub>v</sub>	N/mm <sup>2</sup>	EN 12369-1	860	750	690
Impact resistance	Class	EN 12871	NPD	NPD	NPD
Punshing shear strength R <sub>mean</sub>	N/mm <sup>2</sup>	EN 1195	NPD	NPD	NPD
Punshing shear strength F <sub>ser,k</sub>	N/mm <sup>2</sup>	EN 1195	NPD	NPD	NPD
Punshing shear strength F <sub>max,k</sub>	N/mm <sup>2</sup>	EN 1195	NPD	NPD	NPD
Linear expansion δ <sub>130,85</sub>	mm/m	EN 318	< 3	< 3	< 3
Mechanical durability (kmod; kdef)		Shall be taken from :	EN 1995-1-1	EN 1995-1-1	EN 1995-1-1
Biological durability	Service Class	EN 335	1 & 2	1 & 2	1 & 2
Content of PCP	ppm	EN 13986-5.18	<5	<5	<5

Informative Characteristic	Unit	Reference	Thickness range (mm)		
			>25-32	>25-32	>32
Formaldehyde content	mg/100g	EN 120	< 8 mg/100g DS		
Slip resistance class	Class	DIN 51130	R10	R10	R10
Abrasion resistance	Class	EN 13329 - table 2	AC 4	AC 4	AC 4
Impact resistance (small dia ball)	Class	EN 13329 - table E1	IC 1	IC 1	IC 1
Impact resistentie (large dia ball)	Class	EN 13329 - table E1	IC 1	IC 1	IC 1

Version date :  
6/05/2019

Lode De Boe,  
President UNILIN bvba, division panels

